

PRESSURE PLUGS



THREAD SIZE (NPT)	TPI	FLUSH HEIGHT	CATALOG NUMBER		
			BRASS	ALLOY STEEL	STAINLESS STEEL
1/16	27	0.250	BPP006	APP006	SPP006
1/8	27	0.250	BPP012	APP012	SPP012
1/4	18	0.406	BPP025	APP025	SPP025
3/8	18	0.406	BPP037	APP037	SPP037
1/2	14	0.531	BPP050	APP050	SPP050
3/4	14	0.531	BPP075	APP075	
1"	11-1/2	0.656	BPP100	APP100	
1-1/4	11-1/2	0.656	BPP125		
1-1/2	11-1/2	0.656	BPP150		

- Threadless plugs utilize an expandable O-ring to create a positive seal.
- Seals rough or corroded holes.
- Withstands pressures up to 72 psi.
- No tapping is required.



CATALOG NUMBER	NOMINAL SIZE	HEIGHT	HEX SIZE	DRILL SIZE	O-RING CATALOG NUMBER
TBPP012	1/8	0.50	5/64	11/32	OR-012
TBPP025	1/4	0.56	1/8	7/16	OR-025
TBPP037	3/8	0.62	1/8	9/16	OR-037
TBPP050	1/2	0.62	1/8	11/16	OR-050
TBPP012-OS	1/8	0.50	5/64	23/64	OR-012
TBPP025-OS	1/4	0.56	1/8	29/64	OR-025
TBPP037-OS	3/8	0.62	1/8	37/64	OR-037
TBPP050-OS	1/2	0.62	1/8	45/64	OR-050

- Standard plugs are flush type (7/8" taper per foot).
- Oversize plugs are (Dry Seal). To order add -O/S to catalog number.

O-RING PLUGS

CATALOG NUMBER	R REAM SIZE	B (+.000) (-.005)	D (+.005) (-.000)	REMOVAL THREAD SIZE
OR-06	0.281	1/4	0.250	6-32
OR-12	0.375	5/16	0.312	10-32
OR-25	0.500	5/16	0.312	10-32
OR-38	0.625	7/16	0.437	1/4-20
OR-50	0.750	1/2	0.500	1/4-20
OR-75	1.000	5/8	0.625	3/8-16




- O-Ring plugs are used when backed up by other mold inserts, holder block, etc.
- They require less space than NPT pressure plugs. Less inter-ferece in tight spaces.
- Standard Buna O-Ring provides seal to 210° Farenheit.
- Viton O-Rings and quad rings are available.

HEAVY DUTY PLUGS

CATALOG NUMBER	THREAD SIZE (NPT)
XTBF-006	1/16
XTBF-012	1/8
XTBF-025	1/4
XTBF-037	3/8
XTBF-050	1/2
XTBF-075	3/4

- Standard brass flush seal plugs with **XT** forming technology for maximum wrenching torque.
- Extra deep socket can't "round out" when plugs are installed or removed.
- Order in any quantity.

With Patented **XT** Technology...



Extra deep socket is stronger, and will not strip out.



BSP PLUGS

CATALOG NUMBER	THREAD SIZE (NPT)
MP-012BSP	1/8-28
MP-025BSP	1/4-19
MP-037BSP	3/8-19
MP-050BSP	1/2-14
MP-075BSP	3/4-14
MP-100BSP	1-11

- Fits BSPT and BSPP threaded holes.
- Features extra deep socket for strength.
- Order in any quantity.

STOP PLUGS

CATALOG NUMBER	FITS SOCKET SERIES NUMBER
CP-200	200
CP-300	300
CP-500	500



- Stops coolant flow on hoses with flow-thru sockets.
- Prevents accidents by plugging unused hoses and manifold ports.
- Keeps couplers and seals clean when not in use.