

CUT-OFF WHEELS AND MANDRELS

Catalog No.	Diameter	Thickness	Hole
CW10606	1"	1/16	1/16
CW20306	1-1/4"	1/32	1/16
CW20606	1-1/4"	1/16	1/16
CW30106	1-1/2"	1/64	1/16
CW31212	1-1/2"	1/8	1/8
CW40312	2"	1/32	1/8
CW40612	2"	1/16	1/8
CW40912	2"	3/32	1/8
CW41212	2"	1/8	1/8

HIGH SPEED CUT-OFF WHEELS

Vitrified banded for quick, efficient cutting and blending.

Excellent for cutting slots, ribs and all types of tool steel. Structured to be cool cutting to minimize damage to parts being cut.

Always use approved machine guards/eye protection when cutting or grinding with cut-off wheels.



Catalog No.	Diameter	Thickness	Hole	Max RPM
CWR3031	3"	1/32	1/4	25,000
CWR3062	3"	1/16	1/4	25,000

REINFORCED T-1 CUT-OFF WHEELS

Double reinforced for maximum safety on die grinders and other high speed tools. Grade A60-TBF for smoother cut on ferrous metals.

Always use approved machine guards/eye protection when cutting or grinding with cut-off wheels.



MANDRELS WITH SCREWS FOREDOM

	Cat. No.	Shank	Arbor Hole/ Capacity	Max RPM
	M1	3/32	1/16	40,000
	M10	3/32	1/16	40,000
	M12	1/8	1/8	40,000
	M13	3/32	1/16	30,000
	M14	1/8	1/8	30,000
	M8	1/8	1/4	20,000
	M15	1/8	1/16	40,000
	M19	1/8	1/16	30,000
	M2	3/32	1/8	20,000

	Cat. No.	Shank	Arbor Hole/ Capacity	Max RPM
	M6	1/8	1/16	40,000
	M20	1/8	1/8	20,000
	M3	3/32	3/32	40,000
	M9	1/8	3/32	40,000
	M7	1/8	1/8	40,000
	M83	1/8	1/8	20,000
	M84	1/4	1/8	20,000
	M85	1/4	1/4	20,000